

* PRODUCT INFORMATION *

HUSKEY™ 342 DAMPING GREASE

ОПИСАНИЕ:

HUSKEY™ 342 Damping Grease – blendируется из высокоочищенных синтетических масел, неплавящихся, синтетических загустителей, и легирована высококачественными противозадирными присадками и ингибиторами коррозии. Это пластическая смазка имеет высокую стабильность, минимальное влияние на эластомеры и пластмассы и широкий интервал рабочей температуры (от –40 до +232 °С).

ПРИМЕНЕНИЕ:

HUSKEY™ 342 Damping Grease применяется как демпфирующая смазка для узлов, где требуется точная регулировка. Также это высококачественная смазка для шариковых и роликовых подшипников, втулок, направляющих, и т.д.

ПРЕИМУЩЕСТВА:

- Широкий интервал рабочей температуры
- Не оставляет пятен на поверхностях
- Стойкая к воде и пару
- Уменьшает трение и износ
- Совместима с большинством эластомеров и пластиков

ТЕХНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

ТЕСТЫ	РЕЗУЛЬТАТЫ
Цвет	Прозрачный желтый
Номер консистенции по NLGI	2
Пенетрация, @ 25 °С	280
Масло-основа, Вязкость	
SUS @ 100 °F	575
SUS @ 210 °F	86
cSt @ 40 °С	125
Индекс вязкости	150
Температура застывания, °С	–38
Температура вспышки, °С	+232
Температура каплепадения, °С	Отсутствует
Относительная плотность при 15,6/15,6 °С	0,89

* Приведенные значения типовые и могут варьироваться.

УПАКОВКА

3,79 л ведро; 18,93 л ведро; 56,78 л бочонок; 208,18 л бочка.

The name of this product or group of products is for product identification only. HUSK-ITT Corp./ SPECIALTY LUBRICANTS Corp. makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corp./ SPECIALTY LUBRICANTS Corp. sales personnel are not authorized to amend this warranty limitation.

7/05
06/08_Ru

© Перевод на русский язык [К.В. Гунин](#), 2008.

Web: <http://www.huskey.ru/> ♦ <http://www.huskey.com/>



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-LUBE