

# HUSKEY LUBRICANT CONVERSION CHART

HUSKEY	CLIMAX	BTR (FORMERLY ROCKWELL)	SERVICES
VALVE CHEAT-HER	340 / 600 / 650	386 / 555 / 654 / 921 / 1033	Engineered to release hard-to-operate or frozen valves while maintaining seal. Applications include petroleum, hydrocarbons, aromatics, natural gas and LPG. Contains molybdenum disulfide and graphite.
#2	No Equal	No Equal	A general-purpose, no melt lubricant to be used on worn, scored, or leaky ball or plug valves: contains *Teflon® particles.
#3	600 / 650 / 800	386 / 555 / 654 / 1033	Economical valve sealant for general hydrocarbon, LPG, and aqueous solutions of salts, acids, and caustics.
#4	400 / 400A	147 / 421	Resistant to acids, caustics, aqueous solutions of acids and caustics. **Food and pharmaceutical.
#6	110	N / A	Excellent for body cavities and seat lubrication on gate valves.
#7	711 / 950	357 / 755 / 833 / 950	Gasoline, aviation fuels, mineral oils and other fuel gate valves.
FLUOR-O-LUBE	FL-5	---	Halofluorocarbon lubricant used with oxygen, chlorine, etc.
LUBE "O" SEAL Valve Lubricant Grade USDA H-1 Rated	No Equal	147 / 234 / 386 / 421	USDA H-1 rated for incidental food contact in plug, gate, and other valves used in food, potable water, waste water, or sewage plants.

\*Teflon® is a registered trademark of E.I. duPont deNemours and Company.

\*\*As determined by user.

**IN MOST APPLICATIONS, THE RECOMMENDATION WILL FUNCTION AS LISTED; WE DO NOT WARRANT THE ABOVE IN ALL APPLICATIONS. IF YOU HAVE A SPECIAL PROBLEM, CALL US.**

8/98



## HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:  
1580 Industrial Avenue, Norco, California 92860  
(909) 340-4000 Fax: (909) 340-4011  
www.huskey.com

Eastern Region Office:  
2057 East Aurora Road, Twinsburg, Ohio 44087  
(330) 425-2567 Fax: (330) 425-9637